

Modelos y Precios iluminación Led

Imagen	Modelos	Informacion Técnica	Dimensiones	Potencia	Precio
	VT0901	Item NO: VT0901			
		Input Voltage: AC110V & 220V			
		Power : 9W			
		LED Source Type: SMD3528			
		LED quantity: 144pcs			
		Color Temperature: 2700-3500K or 5700-6500K	Φ30X600mm	9W	36
		Luminous Flux: 950~980Lm			
		Work Frequency: 50-60HZ Beam Angle : ≥120Degrees LED'S Operating Life: 50,000Hours			
	VT1501	Item NO: VT1501			
		Input Voltage: AC110V & 220V			
		Power consumption: 15W			
		LED Source Type: SMD3528			
		LED quantity: 240pcs	Φ30X1200mm	15W	52
		Color Temperature: 2700-3500K or 5700-6500K			
		Luminous Flux: 1580~1700Lm			
		Work Frequency: 50-60HZ Viewing Angle : ≥120Degrees LED'S Operating Life: 50,000Hours			
	VT1801	Item NO: VT1801			
		Input Voltage: AC110V & 220V			
		Power consumption: 18W			
		LED Source Type: SMD3528			
		LED quantity: 288pcs			
		Color Temperature: 2700-3500K or 5700-6500K	Φ30X1200mm	18W	60
		Luminous Flux: 1880~1980Lm			
		Work Frequency: 50-60HZ Beam Angle : ≥120Degrees LED'S Operating Life: 50,000Hours			

		Item NO: VB0501-C			
		Housing Material : Ceramics			
		Power: 5W			
		Socket: E27			
		Input Voltage: AC85-265V			
	VB0501-C	CCT: 2700-3500K or 5700-6500K	Φ60X117	5W	24
		Luminous Flux: 380-450LM			
		Surface color:white			
		Item NO: VB0504			
		Casing : AL			
		Power: 5W			
		Socket: GU10			
	VB0504	Input Voltage: AC85-265V	Φ60X108	5W	21
		CCT: 2700-3500K or 5700-6500K			
		Luminous Flux: 380-450LM			
		Surface color:Silver			
		Item NO: VB0702			
		Casing : AL			
		Power: 7W			
		Socket: E27			
		Input Voltage: AC85-265V			
	VB0702	CCT: 2700-3500K or 5700-6500K	Φ70X129	9W	34
		Luminous Flux: 560~650LM			
		Surface color:Silver or Gold			
	LED Source: 14*0.5W				
	Beam Angle: ≥120 Degrees				
	LED'S Operating Life: 50,000Hours				

		Item NO: VB0703			
		Casing : AL			
		Power: 7W			
		Socket: E27			
		Input Voltage: AC85-265V			
	VB0703	CCT: 2700-3500K or 5700-6500K	Φ60*118	9W	32
		Luminous Flux: 560~650LM			
		Surface color:Silver or Gold			
		LED Source: 14*0.5W			
	Beam Angle: ≥120 Degrees				
	LED'S Operating Life: 50,000Hours				
		Item NO: VB1001			
		Casing : AL+PC			
		Power: 10W			
		Socket:E27			
		Input Voltage: AC85-265V			
	VB100	CCT: 2700-3500K or 5700-6500K	Φ50*168	10W	40
		Luminous Flux: 850-920 LM			
		Surface color:Sliver			
		LED Source:SMD3528 140 PCS *0.06W			
	Beam Angle: 360 Degrees				
	LED'S Operating Life: 50,000Hours				
		Item NO: VB1501			
		Casing : AL+PC			
		Power: 15W			
		Socket:E27			
		Input Voltage: AC85-265V			
	VB1501	CCT: 2700-3500K or 5700-6500K	Φ60*198	15W	51
		Luminous Flux: 1200-1300 LM			
		Surface color:Sliver			
		LED Source:SMD3528 198 PCS *0.06W			
	Beam Angle: 360 Degrees				
	LED'S Operating Life: 50,000Hours				

		Item NO: VP1001			
		Casing : PC			
		Power: 10W			
		Input Voltage: 85-265V AC			
		CCT: 2700-3500K or 5700-6500K			
	VP1001	Luminous Flux: 750-800LM	Φ180XH20	10W	57
		Surface color: Silver			
		LED Source: SMD3528			
		Beam Angle: ≥120°			
		LED'S Operating Life: 50,000Hours			
		UL Transformer			
		Item NO: VP1201			
		Casing : PC			
		Power: 12W			
		Input Voltage: 85-265V AC			
		CCT: 2700-3500K or 5700-6500K			
	VP1201	Luminous Flux: 900~960LM	Φ180XH20	12W	66
		Surface color: Silver			
		LED Source: SMD3528			
		Beam Angle: ≥120°			
		LED'S Operating Life: 50,000Hours			
		UL Transformer			
		Item NO: VP1501			
		Casing : PC			
		Power: 14W			
		Input Voltage: 85-265V AC			
		CCT: 2700-3500K or 5700-6500K			
	VP1501	Luminous Flux: 1010~1200LM	200*200*20	15W	83
		Surface color: Silver			
		LED Source: SMD3528			
		Beam Angle: ≥120°			
		LED'S Operating Life: 50,000Hours			
		UL Transformer			
		Item NO: VP1501			

		UL Transformer			
		Item NO: VP1401			
		Casing : PC+AL			
		Power: 14W			
		Input Voltage: 85-265V AC			
		CCT: 2700-3500K or 5700-6500K			
	VP1401	Luminous Flux: 900-1000LM	300*300*12	14W	138
		Surface color: Silver			
		LED Source: SMD3528 QTY: 192Pcs			
		Beam Angle: ≥120°			
		LED'S Operating Life: 50,000Hours			
		UL Transformer			
		Item NO: VP3001			
		Casing : PC+AL			
		Power: 30W			
		Input Voltage: 85-265V AC			
		CCT: 2700-3500K or 5700-6500K			
	VP3001	Luminous Flux: 1950-2100LM	600*600*12	30W	260
		Surface color: Silver			
		LED Source: SMD3528 QTY: 432pcs			
		Beam Angle: ≥120°			
		LED'S Operating Life: 50,000Hours			
		UL Transformer			
		Item NO: VC0305			
		Casing : AL			
		Power: 3W			
		Input Voltage: AC85-265V			
	VC0305	CCT: 2700-3500K or 5700-6500K	Φ53XH87	3W	22
		Luminous Flux: >240LM			
		Surface color: Silver and Black			
		LED Source: 3*1W			
		Beam Angle: 15° 30° 45° 60°			
		LED'S Operating Life: 50,000Hours			



		Item NO: VC0701			
		Casing : AL			
		Power: 7W			
		Input Voltage: AC85-265V			
	VC0701	CCT: 2700-3500K or 5700-6500K	Φ108XH60	7W	36
		Luminous Flux: >560LM			
		Surface color: Silver			
		LED Source: 7*1W			
		Beam Angle: 15° 30° 45° 60° LED'S Operating Life: 50,000Hours			
		Item NO: VC1201			
		Casing : AL			
		Power: 12W			
		Input Voltage: AC85-265V			
	VC1201	CCT: 2700-3500K or 5700-6500K	Φ137XH68	12W	61
		Luminous Flux: > 1080LM			
		Surface color: Silver			
		LED Source: 12*1W			
		Beam Angle: 15° 30° 45° 60° LED'S Operating Life: 50,000Hours			
		Item NO: VC0902			
		Casing : AL+Glass			
		Power: 9W			
		Input Voltage: AC85-265V			
	VC0902	CCT: 2700-3500K or 5700-6500K	L260*w90	9W	74
		Luminous Flux: > 675LM			
		Surface color: Silver			
		LED Source: 3*3W			
		Beam Angle: 15° 30° 45° 60° LED'S Operating Life: 50,000Hours			

		Item NO: VC1202			
		Casing : AL+PC			
		Power: 12W			
		Input Voltage: AC85-265V			
	VC1202	CCT: 2700-3500K or 5700-6500K	L120*w120	12W	87
		Luminous Flux: > 1080LM			
		Surface color: Silver			
		LED Source: 4*3W			
		Beam Angle: 15° 30° 45° 60° LED'S Operating Life: 50,000Hours			
	Item NO: VF3001				
		Casing : AL+Glass			
		Power: 30W			
		Input Voltage: AC85-265V			
	VF3001	CCT: 2700-3500K or 5700-6500K	L225*185*125	30W	110
		Luminous Flux: > 2700LM			
		Surface color: Silver			
		LED Source: 1*30W (COB)			
		Beam Angle: 95~110° LED'S Operating Life: 50,000Hours			
	Item NO: VW0502				
		Casing : AL+Glass			
		Power: 5W			
		Input Voltage: AC85-265V;50-60HZ			
	VW0502	CCT: 2700-3500K or 5700-6500K;RGB;Yellow	121.5*127.5*34	5W	14
		Surface color: Silver			
		LED Source: 5*1W LED'S Operating Life: 50,000Hours			